UNIFORM STATUTORY DECLARATION FORM FOR THE REGISTRATION OF FITTING DESIGNS

NEW BRUNSWICK NUNAVUT	NOVA SCOTIA YUKON	PRINCE EDWARD ISLAND NORTHWEST TERRITORIES	NEWFOUNDLAND AND LABRADOR
MANUFACTURERS NAME:	Swagelok Company		
MANUFACTURERS ADDRESS	29500 Solon Road, Solon, Ohio 44139 USA		
PLANT LOCATIONS: Headow	larters: 29500 Solor	n Road, Solon, Ohio 44139 USA (See Att	achment ()
CATEGORY OF FITT	NGS TO BE REGISTER	ED. CIRCLE ONE CATEGORY ONLY	INLE OF THE STANDARD OF CONSTRUCTOR
A Pipe fittings, including couplir B Flanges: all flanges C Valves: all flanges DExpension joints, flaxible con E Strainers, filters, separators, o F Measuring devices, including pressure transmitters C Certified capacity-rated press boliers, pressure vessels, pip H Pressure retaining component	nga, tees, elbows, Ys, ptu nections, and hose asser and steam traps pressure gauges, level g ure relief devices accept; fing and fusible plugs is that do not fail into one	gs, unions, pipe caps, or reducers nblies: all types auges, sight glasses, levels, or able as primary over pressure protection on e of the above categories	Rubber Products Manufacturers (ARPM) Hose Handbook
SHOW MANUEACTUREDS NAM	E TRADEMARK OR	D, (Mosting AECB or ASME requirements) DGD AS IT WILL APPEAR ON THE PRODUCT	
Swa	gelok	PIECATION OF THE ACTUAL ITEMS TO BE RE	POROLD D WELDED D WRDUCHT D CAST D OTHER X DESCRIBE OTHER X PTFE Core
amperature ratings, and ident nanufacture of these fittings is of in part and has been varified	the end product do so product for which regis ification markings are is regulated by a Quality d by <u>BSI</u> lieving it to be true, an	lemmiy declare that the information containe- tration is sought. The dimensions, materials in accordance with the herein named standa y Control Program which extends to each plu- as being suitable for the d knowing that it is of the same force and eff	s of construction, pressure rds. I further declare that the ant where fabrication occurs in whole
lignature of Declarer:	hell.7	alter-	
Declared before me at Un	able to get a	notary signature or is	SPACE FOR THE
This day of SCA Commissioner of Oaths or Notary Public: (sign)	Hare to CO eptember 17 Affix Official scal to the r	VID-19 situation OFFI (, 2020 9M0	CIAL SEAL
This r	Thi egistration must be rev	a space for Regulatory Authority use validated after ten (19) years from the date o	
CRN: 0D22748.5		1 Cal	Boilers and
FID#: 1214		Nuñavut	Pressure Vessels Act
Crimped X series PTFE	hose assemblies.	REG	ISTERED
Notes: 1. All fittings shall be registered 2. Each category shall be support forms and one copy of supporting 3. The declaration shall be made responsibility for the quality of the 4. Quality control programs shall at a maximum interval of five (5) <u>CRN expires Oct.16</u>	Inted with two Statutory D g documentation. a by the person having fur a end product. I be resubmitted for valid years.	acturer. eclaration CRN OD22 It authority and Date NOLEM stion Signed	48.5N
		Territorial P	Registration Fee



Canadian Registration Number Submittal Category D Crimped Swagelok X Series PTFE Hose September 1, 2020 Page 1 of 2

Attachment B: Scope of Registration for Crimped Swagelok X Series PTFE Hose Assemblies (Category D)

This document represents the scope of the Swagelok Coreflex XC and XT hose (X Series) and crimped assemblies covered by this submission for CRN approval. These products have been evaluated in accordance with the Association for Rubber Products Manufacturers (ARPM) Hose Handbook.

Summary Table

x	X Maximum Pressure (psig)					
Series Hose Size	At Minimum Temp. (-65°F)	Room temperature (0°-100°F)	At Maximum Temp. (450°F)	Pressure Retaining Material	End Connections and Sizes	Design Code of Construction
1/4"	3500	3500	3075		Swagelok Tube Fitting [SL, SM] 1/8" – 2" (3-50mm)	
3/8"	3000	3000	1675	Core Smooth bore PTFE (XT Series) OR Smooth bore carbon black	Nooth boreMale & Female NPT TaperedTFE (XTPipe Fitting [PM, PF] 1/8" - 2"Series)ORORMale & Female ISO/BSPnooth boreTapered (ISO 7) Pipe Threads	
1/2"	1800	1800	1665	filled PTFE (XC Series) <u>Braid</u> Fiber braid reinforcement	Male 37° JIC & Female 37° JIC with female swivel nut [AN, AS] 1/4" – 2" Tube Butt Welds [TB] 1/2" – 1"	Association for Rubber Products Manufacturers (ARPM) Hose
3/4"	1250	1250	900	Connections 316 SS Crimp on Collar 300 series SS	Female VCO O-ring Face seal Fitting [VF] 1/8" – 2" Female VCR Metal Gasket Face seal Fitting [RF] 1/8" – 2" Male ISO/BSP Parallel Threads	` Handbook
1"	1000	1000	895		W/ 60° Male cone (ISO 228) [MS] 1/4" – 1" Female ISO/BSP Parallel Threads (ISO 228) [FS] 1/4" – 1"	




Canadian Registration Number Submittal Category D Crimped Swagelok X Series PTFE Hose September 1, 2020 Page 2 of 2

XT series is standard Swagelok virgin PTFE-lined hose with a fiber braid reinforcement and 304 stainless steel reinforcement with a silicone cover. The XC series consist of the same construction but has Swagelok carbon black filled virgin PTFE liner. The 1 inch nominal ID hose for both XT and XC series is constructed with two stainless steel braids and no fiber braid. All X Series hoses undergo production testing in accordance with ASTM D380 "Test Methods for Rubber Hose" (version current to hose production date).

Configurations

All end connection inserts are crimped onto the hose using crimp collars.



Product Options:

Additional options that do not affect pressure and/or temperature ratings may be made available and are within the scope of this approval. Examples of these would include, but not limited to, the following:

Cover Options

- Armor guard Interlocking, flexible 302 stainless steel.
- Fire jacket Woven fiberglass coated with specially compounded aerospace-grade silicone rubber
- Spiral guard Helical HDPE plastic

Tag and Marking Options

- Mat tag Polyester tag with customer-specified text
- Lanyard tag Stainless steel tag with customer-specified text

End Connection Seals or Sealants Options

- VCO O-rings
- Pipe Thread ends thread sealant

Quality System

The Swagelok Company quality system complies with the requirements of ISO 9001:2015. The Swagelok Company maintains BSI Certificate of Registration Number FM 01729, which applies to all locations listed on the Certificate.

References

The product catalog does not represent the full scope of the registration but rather details some of the most common options. Hose Assemblies, Bulk Hose, and End Connections Product Catalog MS-01-180.



Attachment A. Swagelok Manufacturing Locations

This document lists the Swagelok locations where end item or component level manufacturing activities take place.

Swagelok Company	Swagelok Company (Falon 1)	
29500 Solon Road	348 Bishop Road	
Solon, Ohio 44139	Highland Heights, Ohio 44143	
USA	USA	
Swagelok Company (Highland)	Swagelok Company (Falon 2)	
318 Bishop Road	358 Bishop Road	
Highland Heights, Ohio 44143	Highland Heights, Ohio 44143	
USA	USA	
Swagelok Company (OFC)	Swagelok Company (HPF)	
29495 F.A. Lennon Drive	6050 Cochran Road	
Solon, Ohio 44139	Solon, Ohio 44139	
USA	USA	
Swagelok Company (Atlantic)	Swagelok Company (Snow Metal)	
26651 Curtiss Wright Parkway	6060 Cochran Road	
Willoughby Hills, Ohio 44092	Solon, Ohio 44139	
USA	USA	
Swagelok Company (Micro) 26653 Curtiss Wright Parkway Willoughby Hills, Ohio 44092 USA	Swagelok Company (Alfred) 29500 Ambina Drive Solon, Ohio 44139	
Swagelok Hose Services Company (SHSC)	Swagelok Company (Strongsville)	
29900 Solon Industrial Parkway	15400 Foltz Road	
Solon, Ohio 44139	Strongsville, Ohio 44119	
Swagelok (China) Fluid System Technologies Ltd.	Swagelok Limited	
Changshu Export Process Zone	Ballafletcher Road	
Changshu Economic Development Zone	Tromode	
Changshu, Jiangshu	IM4 4RA	
215513 China	Isle of Man	